

AQUA MIX® GROUT SEALER

1. Product Name

Aqua Mix Grout Sealer

2. Manufacturer

Custom Building Products
 13001 Seal Beach Blvd.
 Seal Beach, CA 90740-2757
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800-200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com



3. Product Description

Aqua Mix Grout Sealer is a water-based sealer that resists water, oil, and acid-based contaminants.

Aqua Mix Low VOC (Volatile Organic Compound) formulas helps to provide better indoor and outdoor air quality compared to similar traditional products. This product Complies with EPA and CARB VOC Requirements.

KEY FEATURES

- Simplifies maintenance and does not change the appearance of the grout
- Allows moisture vapor transmission

AREAS OF USE:

- Cementitious sanded and unsanded porous grout joints for ceramic tile installations.
- Effective for interior and exterior applications

LIMITATIONS

- Do not allow sealer to dry on tile surface because a residue will be visible. If this occurs, use Aqua Mix Poultice Stain Remover mixed with water into a wet slurry and scrub with a nylon pad
- Do not allow sealer to come in contact with any non-recommended surface
- Sealers will not prevent surface wear or etching from acids or caustic chemicals

4. Technical Data

TEST METHOD	TEST RESULTS
Stain Resistance (CTI 72)	Good
Service Time	12 hours
Full Cure	48 hours

5. Installation

APPLICATION

Read entire label before using. For new installations, sealer can be applied as soon as 48 hours after grouting. Grout joints must be clean, dry, and free of existing sealers or coatings. Apply using a soft-bristle paintbrush or sponge paint applicator. NOTE: Be sure any sealer that does not penetrate surface is removed from surface within 5 minutes of each application using absorbent paper or cotton towels. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats. After 2 hours conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an additional coat. Wait 2 hours and repeat the test. Ready for surface traffic in 2 hours after final coat. Keep area dry for 12 hours. Achieves a full cure in 24 hours. Clean applicator tools with water after each use. May be reapplied as needed to grout joints that are clean.

Coverage

Approximately 300 to 1,500 sq. ft. (30 m² to 139 m²) per coat per gallon (3.8 L), depending on type of stone or tile, porosity and texture of surface, temperature, humidity, and method of application.



Handling and Storage

- Close container tightly after each use
- Store in original container only
- Store and use between temperatures of 50° F and 80° F (10° C and 27° C)

CAUTION

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains glycol ether monobutyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

6. Availability & Cost

Contact the manufacturer or visit custombuildingproducts.com for information about product cost and availability.

	CÓDIGO DE PRODUCTO	TAMAÑO	ENVASE
USA	020721	1 pt (473 ml)	Bottle
USA	020720-4	24 oz (720 ml)	Spray
USA	020723	1 gallon (3.8 L)	Bottle
USA	020724*	5 gallons (19 L)	Pail
USA	020725	55 gallons (210 L)	Drum
Canada	C020721	1 pt (473 ml)	Bottle
Canada	C020728	8 oz (240 ml)	Bottle
Canada	C020723	1 gallon (3.8 L)	Bottle

*Indicates a special order item.

7. Limited Product Warranty

Custom Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom’s sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom’s printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

For details and complete warranty information, visit custombuildingproducts.com

8. Maintenance

Aqua Mix Concentrated Stone & Tile Cleaner or AquaKleen™ or AquaShield™ is recommended for routine spray and wipe cleaning and resealing.

9. Technical Services

For technical assistance contact Custom Building Products or visit custombuildingproducts.com.

10. Filing Systems

Additional product information is available from the manufacturer upon request.

Related Products:

- Aqua Mix®
- AquaShield™ Cleaner & Resealer

